

**BOBCAT COMPANY PRICE PAGES**  
**AT450 Articulating tractor & Attachments**  
**SLP Price List**



**Please note the following when using Steiner Price Pages:**

- All prices are shown in U.S. dollars.
- Prices and specifications are subject to change without notice.

**Effective Date: January 1st, 2025**

**THE FOLLOWING UPDATES HAVE BEEN MADE TO THIS DOCUMENT:**

Date	Description of Change
7/1/2024	Release Mid-Year Pricing
1/1/2025	Updated Price for Flail Mower

\*Certain Specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual Steiner equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.

# AWD Power Unit

## AT450 Bobcat Articulating Tractor



### Standard Equipment

#### Engines

32.5 HP Kubota® WG972 gas, Liquid-cooled, 962 cc  
24.8 HP Kubota® D902 Diesel, Liquid-cooled, 898 cc

#### Standard Tire options

Field Trac / 22x12-10 (All Terrain)

#### Transaxles

(2) Peerless® 2600 dual-range

#### Brakes

Single, mechanical disc

F/R Hand control & Foot Pedal Control

#### Weight Transfer

Hydraulic (on the fly adjustments)

#### Hitch

Front - Quick-Hitch System

Rear - Standard 2" receiver hitch

#### Frame

Oscillating  
Articulating

#### Additional Features

Parking Break  
Dual LED headlights and Taillights  
High-Back bucket seat  
Storage compartment  
Cup Holder  
Front and rear Skid Plates  
ROPS Bar  
12 Volt outlet, 15 amp  
Battery disconnect  
(4) 50lb weights  
Front Fenders  
Foot Pegs  
Engine Overheat Protection Kit

Warranty - 2 Years

### Quick Specs

#### M6001 - Kubota Gas

#### M6001 - Kubota Diesel

Unit weight.....	1860 lbs.	1865 lbs.
Shipping weight.....	2075 lbs.	2080 lbs.
Hydraulic Pump Cap. - Standard Flow.....	6 gpm @ 3600 rpm	
Lift, steering aux pressure.....	1750 PSI	
Hydraulic oil capacity.....	5.25 US Gallons	
Speed Hi Range (Fwd. / Rev).....	9.5 mph / 7 mph	
Speed Low Range (Fwd. / Rev).....	6 mph / 4.5 mph	
Width Standard.....	44.5"	
Width W/ 3" Extensions.....	50.5"	
Width W/ Dual Wheel Kit.....	66.5"	
Overall Length (ROPS Up).....	80.5"	
Height W/ ROPS Up.....	73.5"	
Height W/ ROPS Folded.....	55"	
Wheelbase.....	43.5"	
Frame Oscillation.....	9"	
Turning Radius.....	43.5"	
Slope Rating- Single Tires (std).....	20° Max	
Slope Rating- 3" Wheel Extensions.....	25°	
Slope Rating- Dual Wheel Tires.....	30° Max	
Slope Rating w/ Cab.....	10°	
Fuel Tank Capacity.....	7 US Gallons	

**AWD Power Unit  
AT450**

<b>Part Number</b>	<b>Description</b>	<b>AT450 Tractor</b>	<b>SLP In US \$</b>
--------------------	--------------------	----------------------	---------------------

<b>M6001</b>	AT450 Articulating & Oscillating Tractor.....		\$28,049
--------------	---	--	----------

Est. Set up Time: 1.5 - 2 hours

<b>Part Number</b>	<b>Description</b>	<b>AT450 Engines (Must Select 1 option)</b>	<b>SLP In US \$</b>
--------------------	--------------------	---	---------------------

<b>M6001-R01-C02</b>	32.5 HP Kubota® WG972 gas, Liquid-cooled, 962 cc.....		\$3,400
----------------------	---	--	---------

<b>M6001-R01-C03</b>	24.8 HP Kubota® D902 Diesel, Liquid Cooled, 898 cc.....		\$3,200
----------------------	---	--	---------

**Bar and Turf Tire options can be ordered through parts:**

Bar Tire Wheel Assembly:      4167166 (2x)  
    4167167 (2x)

Turf Tire Wheel Assembly:      4175290 (4x)

\*The Rims on these options will be white

## AT450 Tractor Accessories



Part Number	Description	Dealer Installed Accessories - <b>Order from Parts</b>	SLP In US \$
7536686	<b>Kit Dual Wheel FLD TRX AT (Orange Rims).....</b>		\$ _____
	Available on the AT450 Optional Kit for work on 30° slopes, added floatation, stability and traction  Est. install time: 1.5 - 2 hours		
75-71327	<b>Dual Wheels - Bar Tread, DW327.....</b>		\$ _____
	Available on the AT450 Optional Kit for work on 30° slopes, added floatation, stability and traction  Est. install time: 1.5 - 2 hours		
75-71328	<b>Dual Wheels - Turf, DW328.....</b>		\$ _____
	Available on the AT450 Optional Kit for work on 30° slopes, added floatation, stability and traction  Est. install time: 1.5 - 2 hours		
75-71206	<b>Wheel Spacer Kit - 3", WS200.....</b>		\$ _____
	Available on the AT450 Optional Kit for added stability and traction when working on slopes 25° or less. Not compatible with the Dual Wheel Kit.  Est. install time: 1 hour		
75-71204	<b>WB201 - Weight Kit.....</b>		\$ _____
	Available on the AT450 (4) 50 Lb. weights included (Weights only)  Est. install time: 0.25 hours		
7528340	<b>Weight Bar - Front, WB200.....</b>		\$ _____
	Available on the AT450 Optional kit that provides additional weight on the front of the machine  Est. install time: 0.25 hours		

## AT450 Tractor Accessories

Part Number	Description	SLP In US \$
<b>75-71211</b>	<b>Treadle Pedal Kit.....</b>  Available on the AT450 Optional kit for improving control and making directional changes easier  Est. install time:      0.5 - 1 hour	\$ _____
<b>75-71214</b>	<b>Engine Overheat Protection System.....</b>  Available on the AT450 Optional kit for protecting the engine against overheating.  Est. install time:      1 hour	\$ _____
<b>75-71316</b>	<b>Power Outlet Kit - Front.....</b>  Available on the AT450 Optional kit that provides an on/off switch as well as a momentary reversing switch and directional control of certain attachments.  Est. install time:      1.5 - 2 hours	\$ _____
<b>75-71322</b>	<b>Power Outlet Kit - Rear.....</b>  Available on the AT450 Optional kit that provides an on/off switch as well as a momentary reversing switch and directional control of certain attachments.  Est. install time:      1.5 - 2 hours	\$ _____
<b>75-71228</b>	<b>Slope Meter Kit.....</b>  Available on the AT450 Optional kit that mounts on top of the tractor to indicate the degree of a slope  Est. install time:      0.25 hours	\$ _____

## Tractor Accessories

Part Number	Description	Dealer Installed Accessories - <b>Order from Parts</b>	SLP In US \$
970649	<b>ROPS Canopy Kit.....</b>		\$ _____
	Available on the AT450 Optional hard top canopy to protect against the sun and rain  Est. install time:      0.25 - 0.5 hour		
7528400	<b>Auxilliary Hydraulics Kit - Front and Rear.....</b>		\$ _____
	Available on the AT450 Optional kit that allows for the mounting of a second set of hydraulic couplers in the front and a single set of couplers in the rear of the tractor.  Est. install time:      3 - 4 hours		

## AT450 Deluxe Cab



Part Number	Description	Dealer Installed Accessories - Order From Factory	SLP In US \$
-------------	-------------	---	--------------

7535981	<b>Kit - Deluxe Cab.....</b>		\$6,999
---------	------------------------------	--	---------

Available on the AT450  
Tempered glass windows shield the operator from wind, snow, dust and rain.  
Windows can be vented or removed.

Est. install time: 8 - 10 hours

Part Number	Description	Dealer Installed Accessories - Order From Parts	SLP In US \$
-------------	-------------	---	--------------

75-71221	<b>Water Heater Kit.....</b>		\$ _____
----------	------------------------------	--	----------

Available on the AT450  
Optional kit that provides heat to the interior of the cab.

Est. install time: 2 - 3 hours (Reduced if installed at same time as cab)

75-71229	<b>Quick Disconnect Heater Hose Kit.....</b>		\$ _____
----------	--	--	----------

Available on the Deluxe Cab  
Optional kit that assists in removing water heater kit for easier removal of cab

Est. install time: .25 - .5 hours (Reduced if installed at same time as cab)

75-71309	<b>Deluxe Cab LED Light Kit - Front.....</b>		\$ _____
----------	--	--	----------

Available on the Deluxe Cab  
Optional kit which provides two front LED work lights

Est. install time: 1 - 2 hours (Reduced if installed at same time as cab)

75-71310	<b>Deluxe Cab LED Light Kit - Rear.....</b>		\$ _____
----------	---	--	----------

Available on the Deluxe Cab  
Optional kit which provides one Rear LED work light

Est. install time: 1 - 2 hours (Reduced if installed at same time as cab)

## AT450 Deluxe Cab

Part Number	Description	Dealer Installed Accessories - <b>Order From Parts</b>	SLP In US \$
<b>75-71223</b>	<b>Safety Beacon Light Kit .....</b>		\$ _____
	Available on the Deluxe Cab Optional kit that Increases visibility of the tractor in low light and low visibility situations  Est. install time:        1 - 2 hours (Reduced if installed at same time as cab)		
<b>75-71224</b>	<b>Circulating Fan.....</b>		\$ _____
	Available on the Deluxe Cab Optional kit that helps circulate air to help keep the operator cool inside the cab  Est. install time:        1 - 2 hours (Reduced if installed at same time as cab)		
<b>75-71225</b>	<b>Two Side Exterior Mirror Kit.....</b>		\$ _____
	Available on the Deluxe Cab Optional kit that provides an exterior mirror on each side of the cab  Est. install time:        0.5 - 1 hour (Reduced if installed at same time as cab)		
<b>75-71226</b>	<b>Interior Mirror .....</b>		\$ _____
	Available on the Deluxe Cab Optional kit that provides a mirror inside of the cab  Est. install time:        0.5 - 1 hour (Reduced if installed at same time as cab)		



## Bucket - General Purpose



### Quick Specs

	<b>SS248</b>
Overall width.....	52"
Overall height.....	15.25"
Overall length.....	33"
Width of bucket.....	48"
Bucket capacity.....	4 1/2 cubic ft.
Dumping.....	Hydraulic
Scarifier teeth.....	6 - 1" wide (optional)
Weight.....	170 lbs.

Part Number	Description	Bucket - General Purpose	SLP In US \$
-------------	-------------	--------------------------	--------------

7448570	Bucket - General Purpose.....	\$2,249
---------	-------------------------------	---------

Available on the AT450  
 Easily move, lift or haul wet and dry material. Also ideal for excavating small areas.  
 \*Part number is same as 7526583

Est. install time:        1.5 - 2.5 hours

Part Number	Description	Optional - Dealer Installed Accessories - Order From Parts	SLP In US \$
-------------	-------------	--	--------------

78-043	Scarifier Wear Edge.....	\$ _____
--------	--------------------------	----------

Available on 7448570  
 Optional kit that assists with digging and scraping materials and will help protect the front edge of the bucket

Est. install time:        0.5 - 1 hour

## Finish Mower Decks 61" & 72" AirFX



### Quick Specs

	<u>61" AirFX™</u>	<u>72" AirFX™</u>
Overall Width.....	76.5" (194.3 cm) w/ discharge	86.9" (220.8 cm) w/ discharge chute
Cutting Width.....	61" (155.5 cm)	71.5" (181 cm)
Cutting Height.....	1" to 5"	1" to 5"
Spindle Drive.....	Single "V" belt	Single "V" belt
Spindles.....	Deep groove double sealed	Deep groove double sealed
Blades.....	3 Blades, 21"	3 blades, 24.5"
Discharge.....	Side	Side
Caster Wheels.....	11" x 6" Semi Pneumatic	11" x 6" Semi Pneumatic
Weight.....	540 lbs	600 lbs
Hydraulic Flip-up.....	Standard	Standard
Drive:.....	Shaft to PTO Belt	Shaft to PTO Belt

Part Number	Description	SLP In US \$
<b>7526579</b>	<b>AirFX™ Finish Mower - 61" .....</b>	<b>\$5,199</b>
	Available on the AT450	
	Rotary finish mower with AirFX™ technology which includes the bolt on baffles and Air-Gap baffle system which allows for exceptional quality of cut while maintaining a clean deck. Standard with hydraulic flip up and a striping roller.	
	Required PTO Belt: 4174756	
	Est. install time: 1 hour	
<b>7526575</b>	<b>AirFX™ Finish Mower - 72" .....</b>	<b>\$5,499</b>
	Available on the AT450	
	Rotary finish mower with AirFX™ technology which includes the bolt on baffles and Air-Gap baffle system which allows for exceptional quality of cut while maintaining a clean deck. Standard with hydraulic flip up and a striping roller.	
	Required PTO Belt: 4174756	
	Est. install time: 1 hour	

## Finish Mower Decks 61" & 72" AirFX

Part Number	Description	Optional - Dealer Installed Accessories - Order From Parts	SLP In US \$
----------------	-------------	--	--------------

<b>970567</b>	<b>Kit - ECO plate, 61".....</b>	\$ _____
---------------	----------------------------------	----------

Available on the 61" AirFX™ Deck

Tool-less installation of the ECO plate restricts the discharge chute from dispersing clippings.

Est. install time:            0.25 hours

<b>970634</b>	<b>Kit - ECO plate, 72".....</b>	\$ _____
---------------	----------------------------------	----------

Available on the 72" AirFX™ Deck

Tool-less installation of the ECO plate restricts the discharge chute from dispersing clippings.

Est. install time:            0.25 hours

<b>970588</b>	<b>Kit - Mulch 61".....</b>	\$ _____
---------------	-----------------------------	----------

Available on the 61" AirFX™ Deck

Optional kit that closes off discharge chute and mulches clippings

Est. install time:            1 hours

## Rough Cut Mower



### Quick Specs

	<b><u>Rough Cut</u></b>
Overall width.....	73" (deck 76" with skids)
Cutting width.....	72"
Cutting height.....	3 3/4" - 6"
Drive.....	Shaft to PTO belt
Spindles.....	Cast-iron, sealed ball bearings
Blades.....	3 blades, 24"
Discharge.....	Rear discharge - flexible front and rear shields
Skid Shoe.....	2 skid shoes that allow deck to evenly cut all types of terrain without damaging the mower or the ground
Weight.....	515 lbs.

Part Number	Description	SLP In US \$
<b>7527214</b>	<b>Rough Cut Mower.....</b>	<b>\$4,599</b>
	Available on the AT450 Tackles overgrown brush and bramble up to 1 1/2" in diameter. Requires (4) rear weights	
	Required PTO Belt:      4169475	
	Est. install time:      0.5 - 1 hour	

Part Number	Description	SLP In US \$
<b>75-71302</b>	<b>Counter Clockwise Blade Rotation Kit.....</b>	<b>\$_____</b>
	Available on the Rough Cut Optional kit for creating finer sizing of cut material	
	Est. install time:      2 - 3 hours	

## Flail Cutter



### Quick Specs

	<b>Flail</b>
Overall width.....	78.7"
Overall Length.....	41.6"
Overall Height.....	16.1"
Maximum working width.....	72"
Number of Knives.....	
"Y" Knives.....	72
"Scoop" Knives.....	36
Height of Cut.....	1" - 3"
Height of cut Adjustment Increments.....	1/2"
Striping roller.....	Yes
Tie Down Points.....	4
Weight.....	490 Lbs.

Part Number	Description	Flail Cutter	SLP In US \$
7450787	<b>Flail Cutter.....</b>  Available on the AT450 Effectively cuts through tall, heavy grass and brush up to 3/4" diameter with the "Y" blades and provides a great finish cut with the optional "Scoop blades." *Part number is same as 7526587  Required PTO Belt:      81-BX44  Est. install time:      0.5 Hours		\$7,999

Part Number	Description	Optional - Dealer Installed Accessories - Order From Parts	SLP In US \$
7462681	<b>Kit Flail 72 Finish Blades.....</b>  Available on 7450787 36 Finish cut blades provides a clean finish cut  Est. install time:      0.75 Hours		\$_____

## Straight Blades 48", 60" & 72"



### Quick Specs

	<u>SB48</u>	<u>SB60</u>	<u>SB72</u>
0° Blade Width.....	48"	60"	72"
30° Angled Blade Width.....	44.2	54.6	64.9
Overall length.....	32.5"	32.5"	32.5"
Blade height from cutting edge.....	19.2	19.2	19.2
Weight.....	205 lbs.	225 lbs.	248 lbs.
Hydraulic Angling.....	30° left and right		
Skid shoe.....	Adjustable - .25" increment		
Forward tilt.....	Mechanical On/Off - Spring trip		
Reversible cutting edge.....	3/8" x 4" through hardened steel		

Part Number	Description	SLP In US \$
-------------	-------------	--------------

<b>7453805</b>	<b>SB48 - Straight Blade - 48".....</b>	<b>\$1,695</b>
----------------	---	----------------

Available on the AT450

Hydraulically angle the blade up to 30° left or right for efficient move material such as dirt or snow

Est. install time: 1 hour

<b>7453799</b>	<b>SB60 - Straight Blade - 60".....</b>	<b>\$1,795</b>
----------------	---	----------------

Available on the AT450

Hydraulically angle the blade up to 30° left or right for efficient move material such as dirt or snow

Est. install time: 1 hour

## Straight Blades 48", 60" & 72"

Part Number	Description	Straight Blades	SLP In US \$
----------------	-------------	-----------------	--------------

7453804	SB72 - Straight Blade - 72".....		\$1,895
---------	----------------------------------	--	---------

Available on the AT450

Hydraulically angle the blade up to 30° left or right for efficient move material such as dirt or snow

Est. install time:                      1 hour

## V-Blade BD358



### Quick Specs

	<b>BD358</b>
Overall width.....	69 1/4"
Cutting width	
- Straight.....	58"
- Scoop.....	49"
- V-Blade.....	53"
Overall height.....	21"
Overall length.....	31"
Blade height from cutting edge.....	21"
Angling.....	30° left and right, front and back
Skid shoes.....	Adjustable
Forward tilt.....	Spring-loaded
Cutting edge, 2 position.....	3/8" x 4" hardened
Weight.....	248 lbs.

Part Number	Description	V-Blade	SLP In US \$
----------------	-------------	---------	--------------

<b>7526607</b>	<b>BD358 - Blade, V-Blade.....</b>	<b>\$3,599</b>
----------------	------------------------------------	----------------

Available on the AT450

Quickly move between 4 different angled positions to move snow quickly and efficiently. Requires Front Power Outlet Kit.

Est. install time:            0.5 - 1 hour



## Angle Broom 52AAB



### Quick Specs

	<u>52AAB</u>
Overall width.....	63"
Overall height.....	28.5"
Overall length.....	60"
Brush width.....	52"
Brush diameter.....	26"
Working width.....	52"
Hydraulic angling (Left or Right).....	25°
Speed of brush.....	47 "
Ground clearance.....	Replaceable Polypropylene
Drive.....	Variable-speed, hydraulic
Weight.....	395 lbs.
Brush Rotation.....	Forward and reverse

Part Number	Description	Angle Broom	SLP In US \$
----------------	-------------	-------------	--------------

7481124	52AAB - Angle Broom.....		\$6,699
---------	--------------------------	--	---------

Available on the AT450

Efficiently remove debris such as dirt, snow or grass from sidewalks, driveways and paved areas.

Est. install time:                      1 hour

## Flex Deck Mower FD800



### Quick Specs

	<b><u>FD800</u></b>
Overall Cutting Width:.....	80"
Transport Width:.....	70" (with trim side deck raised)
Deck Configuration:.....	4 decks with four 21" high-lift blades (1" overlap between decks)
Trim Side Deck:.....	20" offset with hydraulic lift
Spindles:.....	Cast steel with sealed ball bearings
Height of Cut:.....	1.0" – 4.5" in 1/4 inch increments
Deck Articulation:.....	10 degrees up and down from horizontal, 20 degrees total per deck;
Construction:.....	7-gauge steel top and skirts on center deck and 11-gauge on outer decks
Caster Wheels:.....	5 front, 2 rear suspension wheels, 9 x 3.5 no-flat, semi-pneumatic tires with tapered roller bearings and greaseable hubs
Blades:.....	High-lift blades standard, low-lift or mulching blades available
Side Discharge:.....	Optional mulching kit available
Weight:.....	760 lbs

Part Number	Description	Flex Deck Mower	SLP In US \$
7526591	FD800 - Flex Deck Mower - 80".....		\$11,999
	Available on the AT450		
	Mow uneven turf and undulating terrain without scalping and give level playing fields a smooth, professional cut. Great around sand traps, tee boxes and pond banks.		
	Requires (4) rear weights		
	Required PTO Belt:	4174756	
	Est. install time:	2 - 3 hours	

Part Number	Description	Optional - Dealer Installed Accessories - Order from Parts	SLP In US \$
75-71313	KIT - Mulching Baffle.....		\$_____
	Available on the Flex Deck		
	Optional kit that closes off discharge chute and creates a mulching effect and rear discharge.		
	Est. install time:	0.5 - 1 hour	

## Commercial Snow Blower SB648



### Quick Specs

	<u>SB648</u>
Overall width:.....	48"
Overall length:.....	44"
Opening size:.....	27" high x 48" wide
Serrated auger:.....	16" diameter, open center
Blower:.....	18" diameter, 4 blades, 7" depth
Width of cut:	
Standard.....	48"
With optional extension wings.....	52"
Auger speed:.....	140 RPM
Blower speed:.....	700 RPM
Chute:.....	Approximately 7" diameter, 223° rotation
Height of cut:.....	Adjustable skid shoes, 0" to 3/4"
Weight:.....	450 lbs

Part Number	Description	Commercial Snow Blower	SLP In US \$
<b>7526595</b>	<b>SB648 - 48" Professional Snow Blower.....</b>		<b>\$5,499</b>
	Available on the AT450		
	Quickly clear the heaviest snow in tough conditions. Works great for commercial or residential applications.		
	Required PTO Belt:	4165834	
	Est. install time:	2 - 3 hours	

Part Number	Description	<b>Optional - Dealer Installed Accessories - Order from Parts</b>	SLP In US \$
<b>75-71234A</b>	<b>SB648 - Electric Chute Deflector.....</b>		<b>\$ _____</b>
	Available on SB648		
	Optional kit that allows the chute deflector to be operator from the operator's seat.		
	Requires Front Power Outlet Kit		
	Est. install time:	1 - 2 hours	

## Commercial Snow Blower SB648

<b>Optional - Dealer Installed Accessories - Order from Parts</b>		
Part Number	Description	SLP In US \$

<b>75-71235</b>	<b>SB648 - Drift Cutters (1 Set).....</b>	\$ _____
-----------------	---	----------

Available on SB648

Optional kit that helps to cut into snow banks that are taller than the auger.

Est. install time:      0.25 - 0.5 hours

<b>75-71236</b>	<b>SB648 - Extension Wings (4" total, 2" side, 1 set).....</b>	\$ _____
-----------------	--	----------

Available on SB648

Optional kit that widens the swath of the snow blower from 48" to 52" (2" wider on each side)

Est. install time:      0.25 - 0.5 hours

**Aerator**  
**AE60**



**Quick Specs**

	<u><b>AE60</b></u>
Overall width.....	66.81"
Working Width.....	60"
Overall Height.....	31.5"
Overall Length.....	62"
Total Tine Wheels.....	12
Tines/Wheel.....	6
Aeration Pattern.....	1.75" x 4.78"
Maximum Aeration Depth.....	3.5"
Weight.....	750 lbs.

Part Number	Description	Aerator	SLP In US \$
----------------	-------------	---------	--------------

7495996

AE60 - Aerator - 60".....

\$4,499

Available on the AT450

Core aerator with72 total tines providing an aeration patern of 1.75 in. x 4.78 in.

Est. install time:

1 hour

## Turbine Blower PB200



### Quick Specs

	<u>PB200</u>
Overall width.....	27"
Overall height.....	33"
Overall length.....	67"
Air flow.....	8000 cfm
Wind Speed.....	114 mph
Wind speed (deflected to front).....	78 mph
Sound level (while in operator seat).....	91 dBA
Weight.....	235 lbs.
Weight on Casters.....	195 lbs.

Part Number	Description	Turbine Blower	SLP In US \$
7526599	PB200 - Blower, Power Turbine.....		\$6,799
	<p>Available on the AT450</p> <p>Powerful axial-flow turbine design runs quietly and produces wind speeds of 114 MPH. Hydraulically rotate the nozzle 360°.</p> <p>Required PTO Belt:      81-B041</p> <p>Est. install time:      0.5 - 1 hour</p>		

## North America Destination Charges

Part Number	Description	Freight Cost
M6001	AT450 Articulating & Oscillating Tractor.....	\$401
7526579	AirFX™ Finish Mower - 61".....	\$168
7526575	AirFX™ Finish Mower - 72".....	\$168
7448570	Bucket - General Purpose.....	\$111
7527214	Rough Cut Mower.....	\$168
7450787	Flail Cutter.....	\$168
7526595	SB648 - 48" Professional Snow Blower.....	\$168
7526607	BD358 - Blade, V-Blade.....	\$111
7526599	PB200 - Blower, Power Turbine.....	\$111
7526591	FD800 - Flex Deck Mower - 80".....	\$168
7453805	SB48 - Straight Blade - 48".....	\$111
7453799	SB60 - Straight Blade - 60".....	\$111
7453804	SB72 - Straight Blade - 72".....	\$111
7481124	52AAB - Angle Broom.....	\$111
7495996	AE60 - Aerator - 60".....	\$111
7535981	Kit - Deluxe Cab.....	\$111

*For Shipments outside of North America, Please contact Customer Service for Freight Charges*